

Features Torsion Axles

Delta

600 HD



Heavy Duty Livestock Trailer

Scan for more info
on this model!



Delta

DELTA TRAILERS • 1-800-556-2283 • www.deltatrailers.com



600 HD

HEAVY DUTY LIVESTOCK TRAILER

S P E C I F I C A T I O N S

G.V.W.R	14,000#
COUPLER	2 5/16" Gooseneck Coupler
AXLES	Tandem 7,000#
SUSPENSION	Dexter Torflex
BRAKES	Electric Brakes on All Axles
TIRE	16" Radial
WHEEL	16", 8-bolt
SPARE	Full Spare with Carrier
FRAME	3 x 3 Angle
GOOSENECK	6" Channel
CROSSMEMBERS	2 x 2 Angle on 16" Centers
JACK	12,000# Drop Leg Jack (Spring-Loaded)
FLOOR	2" Pressure Treated Pine
SIDES	48" High Embossed, 16 Gauge
SIDE UPRIGHTS	1 x 2 Tubing on 20" Centers
SIDE DOOR	Full Escape Door
ROOF	18 Gauge Metal with Bows on 24" Centers
ROOF RADIUS	6" Roof Radius
NOSE CAP	Round or Square (other nose styles optional)
SAFETY CHAINS	5/16" Heavy Duty with Safety Latch Hooks

CENTER GATE	Heavy Duty Gate with Spring-Loaded Slam Latch
REAR DOOR	Heavy Duty Full Swing with 1/2 Slider
REAR OPENING	Tubing Uprights with Slam Latch for Gate
GOOSENECK GATE	Standard Gooseneck Gate
FENDERS	Steel Teardrop
WINDOWS	None
WIRING	14 Gauge in Conduit with Junction Box
ELECTRIC PLUG	7-Way RV Style
INTERIOR LIGHTS	Standard Dome Lights
EXERIOR LIGHTS	All DOT Required Lighting plus Quad Tail Lights
PRE-PREP	3-Step Acid Washed with Phosphorus Solution
PREP	Exterior Joints and Interior Roof Sealed
PRIMER	Rust Resistant Epoxy Primer
PAINT	Baked-on High Solid Urethane
PINSTripES	Painted Pinstripes
DECK HEIGHT	Approx. 14"
GRAVEL GUARD	Aluminum Diamondplate
REFLECTIVE TAPE	Required D.O.T. Reflective Taping
SAFETY	Emergency Breakaway Switch & Battery Backup

LENGTH	WIDTH	HEIGHT	CENTER GATE
16'	6'	6'6"	Set in Center
18'	6'	6'6"	Set in Center
20'	6'	6'6"	Set in Center
22'	6'	6'6"	Set in Center
24'	6'	6'6"	2 Gates
26'	6'	6'6"	2 Gates
28'	6'	6'6"	2 Gates
30'	6'	6'6"	2 Gates
32'	6'	6'6"	2 Gates
34'	6'	6'6"	2 Gates
36'	6'	6'6"	2 Gates

O P T I O N S

- 6'8" Width \$619 Full Spare (Tire & Wheel) INCL.
- 7' OR 7'6" Width (axle upgrade may be required)
- Extra Interior Light • 8' Width (axle upgrade may be required)
- Extra Center Gate • 6" Additional Height (per 6")
- Add Slider to standard Center Gate
- Smooth Sides (14 gauge) per ft.
- Solid Rear Gate (no slider) • Add 3rd 7,000 lb. axle
- Full Rear Drop Ramp (with mat) • V-Nose Front

