

Features Torsion Axles

Delta

CATTLEMAN



Heavy Duty Livestock Trailer

Scan for more info
on this model!



Delta

DELTA TRAILERS • 1-800-556-2283 • www.deltatrailers.com



CATTLEMAN

OPEN-TOP LIVESTOCK CARRIER

SPECIFICATIONS

G.V.W.R	14,000# to 21,000#	CENTER GATE	Heavy Duty Gate with Vertical Runners & Slam Latch
COUPLER	2 5/16" Gooseneck Coupler	REAR DOOR	Heavy Duty Butterfly Cattle Gates with Pipe Latch
AXLES	7000# and 8000# available	REAR OPENING	Heavy Duty Tubing Uprights
SUSPENSION	Dexter Torflex Suspension	REAR BUMPER	3" Steel Pipe with Wrap Around Corners
BRAKES	Electric brakes on all axles	FENDERS	3/16" Solid Steel Plate - Brush Fenders
TIRE	16" 10-ply radial trailer tires (ST)	WIRING	14 gauge in Conduit with Junction Box
WHEEL	16" Steel Wheel, 8-Hole	ELECTRIC PLUG	7-Way RV Style
SPARE	Full Spare with Carrier	INTERIOR LIGHTS	None
FRAME	3 x 3 Angle	EXTERIOR LIGHTS	All DOT Required Lighting plus Quad Tail Lights
GOOSENECK	Tandems use 8" Channel, Triples use 10" Channel	PRE-PREP	3-Step Acid Washed with Phosphorus Solution
FRONT UPRIGHT	6" Channel with Pipe Bow Reinforcement	PRIMER	PPG® Rust Resistant Primer
CROSSMEMBERS	4" channel on 4' centers with three 3" channel runners	PAINT (BAKED ON)	PPG® Automotive-grade High Solid Urethane
JACK	12,000# Drop Leg Jack (Spring-Loaded)	PINSTRIPES	Painted Pinstripes
FLOOR	2" Pressure Treated Pine, crossways with spaces	DECK HEIGHT	Approx. 14"
SIDES	Open Sides with 1x3 tubing runners	GRAVEL GUARD	Aluminum Diamondplate
SIDE UPRIGHTS	Steel Pipe Bows	REFLECTIVE TAPE	Required D.O.T. Reflective Taping
SIDE DOOR	36" Wide, Full Escape Door	SAFETY	Emergency Breakaway Switch & Battery Backup
ROOF	Pipe Bows with Supporting Steel Rods	SAFETY CHAINS	3/8' Heavy Duty with Safety Latch Hooks
ROOF RADIUS	6" Roof Radius		
NOSE	Open Cage		

Length	Width	Height	Center Gate	Axle
16 ft.	6' 8"	6' 6"	Set in Center	Tandem 7000 # Torsion
18 ft.	6' 8"	6' 6"	Set in Center	Tandem 7000 # Torsion
20 ft.	6' 8"	6' 6"	Set in Center	Tandem 7000 # Torsion
22 ft.	6' 8"	6' 6"	Set in Center	Tandem 7000 # Torsion
24 ft.	6' 8"	6' 6"	2 Gates	Tandem 7000 # Torsion
26 ft.	6' 8"	6' 6"	2 Gates	Tandem 7000 # Torsion
28 ft.	6' 8"	6' 6"	2 Gates	Tandem 7000 # Torsion
30 ft.	6' 8"	6' 6"	2 Gates	TRIPLE 7000 # Torsion
32 ft.	6' 8"	6' 6"	2 Gates	TRIPLE 7000 # Torsion
34 ft.	6' 8"	6' 6"	2 Gates	TRIPLE 7000 # Torsion
36 ft.	6' 8"	6' 6"	2 Gates	TRIPLE 7000 # Torsion



OPTIONS

- 7' OR 7' 6" Width
- 6" Additional Height (per 6")
- Add for Canvas Top (per trailer ft.)
- Add for Metal Top (per trailer ft.)
- 7200# Axle upgrade (9/16" studs, Oil Bath, 12 1/4" x 2 1/4")
- Spring Axles (in lieu of Torsion Axles)
- Solid Rear Gate (no slider)
- Full Swing Rear Gate with 1/2 Slider
- Extra Center Gate
- Extra 7,000 Lb. Axle (tandem axle models only)
- Upgrade to 8,000 Lb. Axle
- Heavy-Duty Cleated Rubber Floor
- Full Nose (to the point where frame tapers down)

