210HGN Low-Pro 10K Dually Gooseneck with 9' Hydraulic Dovetail

G.V.W.R	23,400#		**Electric Plug**	7-Way RV Style
Coupler	2 5/16" E-Z Adjustable Coupler		**Prep**	3-Step Acid Washed with Phosphorus Solution
Axles	Tandem 10,000# Dual Wheel (Oil-Bath)		**Primer**	Rust Resistant Epoxy Primer
Suspension	Multi-leaf Slipper Spring with Equalizer		**Paint**	High Solid Urethane
Tire	ST235/80R16 (10 ply)		**Pinstripes**	Painted Pinstripes
Wheel	16 x 6 Dual 8-bolt		**Overall Width**	102" wide (approx)
Frame	12" I-Beam (**Low-Pro Pierced Beam)**		**Deck Height**	Approx. 33" standard (Low-Pro Pierced Beam)
Neck	12" I-Beam		**Brakes**	Electric brakes on all axles
Crossmembers	3" Channel on 16" centers - Pierced thru Main		**Dove Tail**	**9' Self-Contained Hydraulic Dove Tail**
Safety Chains	3/8' Heavy Duty with Safety Latch Hooks		**Steps**	Access Step on driver's side
Jack	12,000# Spring Loaded Drop Leg Jack		**Storage**	Chain Basket between uprights
Side Rails	5" Angle Iron with Rub Rails		**Wiring**	Front Mount in conduit
Stake Pockets	Formed Stake Pockets on 24" centers		**Reflective Tape**	Required D.O.T. Reflective Taping
Floor	2" Pressure Treated Pine		**Safety**	Emergency Breakaway switch & battery backup
Lights	All LED Stop, Tail, Turn and Clearance			All specifications subject to change without notice.

Fast • Simple • Convenient

No need for Ramps!

All measurements are approximate

Suggested Retail Price

Model	Length	
210HGN-27	27'	
210HGN-29	29'	
210HGN-32	32'	
210HGN-34	34'	
210HGN-36	36'	
210HGN-40	40'	

Dove Tail Description

Dove Tail	Type	Description	MSRP
DT 1	**9' Hydraulic Dove Tail**	Fully self-contained with twin hydraulic cylinders plus pump, battery and remote	Included

Overall trailer length includes dove tail length

210HGN Options Pricing

Electric over Hydraulic Brakes		Torque Tube (helps minimize trailer twisting)	
Disc Brakes (Includes 10K HD) (must add elec/hyd. brake		Pipe Spools (between Stake Pockets)	
Dexter HD Adjustable Suspension (similar to Hutch)		Extend Metal Track & add 1/2" angle traction cleats (6" OC)	
Front Toolbox (between jacks) with lockable Lid		Spare (Complete Tire & Wheel)	
Side Mount Toolbox with lid (18" x 14" x 36")		Upgrade to 12K Axles	
Extra Spring Loaded Jack (Dual Jacks)		Upgrade to 12", 22 lbs. I-Beam	
2-Speed Jack System (includes 2nd Jack)		Upgrade to 14-ply radial tires	
2-Hydraulic Jacks (includes separate pump & battery)		Upgrade to 17.5 tires (each tire)	
Deck over Gooseneck (welded-on) (96" x 72")		Weld-on or Sliding Ratchets	
Metal Floor (3/16" Diamondplate with crossmembers on 12" centers)		Ratchet Rail (per 6' length)	