


Bumper-Pull Model

G.V.W.R	14,000#	HYDRAULIC LIFT	Self-Contained Electric/Hydraulic Scissor Lift
COUPLER	2 5/16" Bulldog Coupler on Leveler Track	HYDRAULIC PUMP	Front Mount Pump & Battery inside toolbox
AXLES	Tandem 7,000# Single Wheel	CONTROL	Magnetic Control Unit
SUSPENSION	Multi-leaf Slipper Spring with Equalizer	DUMP BED SIDES	19" high, 12 gauge smooth steel
BRAKES	Electric brakes on all axles	REAR GATE/DOOR	Combination Dump/Swing gate with Cam Latches
TIRE	ST235/80R16 (10 ply)	LOADING RAMPS	2 - 6 ft. Loading Ramps
WHEEL	16 x 6, 8-bolt Steel	LIGHTS	All LED Stop, Tail, Turn and Clearance
FRAME	10" I-Beam (12 lbs./ft.)	ELECTRIC PLUG	7-Way RV Style
TONGUE	10" I-Beam (12 lbs./ft.)	PREP	3-Step Acid Washed with Phosphorus Solution
CROSSMEMBERS	3" Channel	PRIMER	Rust Resistant Epoxy Primer
BED CROSSMEMBERS	3" Channel on 12" centers	PAINT	High Solid Urethane
BED LONG SILS	3" Channel	PINSTRIPES	Painted Pinstripes
SAFETY CHAINS	Heavy Duty with Safety Latch Hooks	WIDTH	96" wide (approx.)
JACK	12,000# Spring Loaded Drop Leg Jack	FLOOR HEIGHT	Approx. 33"
BED TIE DOWNS	4-Heavy Duty D-Rings	STORAGE	Front Mounted Toolbox with Lid (in A-Frame)
FLOOR	10 gauge smooth steel	WIRING	Front Mount in conduit
FENDERS	none	REFLECTIVE TAPE	Required D.O.T. Reflective Taping
DUMP ANGLE	45 degree Dump Angle (max)	SAFETY	Emergency Breakaway switch & battery backup
TARP/MOUNT	Tarp Mount is Standard, Tarp Optional		All specifications subject to change without notice.

Measurements

Length	A	B	C
12	144	81	33"
14	168	102	33"
16	192	118	33"



SUGGESTED RETAIL PRICE

Bumper Pull

Model	Length	Capacities
27BD-12	12'	5.6 cubic yards
27BD-14	14'	6.6 cubic yards
27BD-16	16'	7.5 cubic yards

27BD OPTIONS PRICING

Extra Spring Loaded Jack (Dual Jacks)		Spare (Complete Tire & Wheel)	
2-Speed Jack System (includes 2nd Jack)		Upgrade to 14-ply radial tires	
Debris Tarp		Upgrade to 17.5 tires (each tire)	
		Rear Stabilizer Drop Legs	