CARGO 300TG — Tandem Axle Enclosed Trailer (Gooseneck)

G.V.W.R	7,000 # to 10,400 #		**Side Door**	Full Size
Coupler	2 5/16" Gooseneck Coupler		**Exterior Lights**	D.O.T. Stop, Tail, Turn and Clearance
Axles	Tandem 3,500#, Tandem 5,200# Dexter		**Interior Lights**	2 Dome Lights (1 near each door)
Suspension	Eye-to-Eye Springs with Equalizer		**Electric Plug**	7-Way RV Style
Brakes	Electric brakes on all axles		**Wiring**	14 gauge in Conduit with Junction Box
Tire	16" Radials (15" radials on 14' and under)		**Pre-Prep**	3-Step Acid Washed with Phosphorus Solution
Wheel	16", 6-bolt (15" wheels on 14' and under)		**Prep**	Joints sealed with Polyurethane sealant
Frame	3 x 3 Angle		**Primer**	Rust Resistant Epoxy Primer
Gooseneck	6" Channel		**Paint**	Baked-on High Solid Urethane
Crossmembers	2 x 2 Angle on 16" centers		**Pinstripes**	Painted Pinstripes
Safety Chains	3/8' Heavy Duty with Safety Latch Hooks		**Box Width**	72" approx. standard
Jack	10,400# Spring-Loaded		**Deck Height**	Approx. 14"
Sides	14 gauge smooth skin		**Gravel Guard**	Aluminum Diamondplate
Side Uprights	1 x 2 Tubing on 20" centers		**Graphics**	Optional
Floor	3/4" Treated Pine		**Wiring**	Front Mount in conduit
Roof	18 gauge Metal with Bows on 24" centers		**Reflective Tape**	Required D.O.T. Reflective Taping
Rear Door	Double Rear Van Doors		**Safety**	Emergency Breakaway switch & battery backup

Suggested Retail Price

Length	Width	Height	Axle	Tires	MSRP
12'	6'	6'	Tandem 3500 # Spring	15" Radial	
14'	6'	6'	Tandem 3500 # Spring	15" Radial	
16'	6'	6'	Tandem 3500 # Spring	16" Radial	
18'	6'	6'	Tandem 5200 # Spring	16" Radial	
20'	6'	6'	Tandem 5200 # Spring	16" Radial	
22'	6'	6'	Tandem 7000 # Spring	16" Radial	
24'	6'	6'	Tandem 7000 # Spring	16" Radial	

Options Pricing

6'8" Width		5200# axle Torsion (in lieu of 3500# axles) tandem	
7' OR 7'6" Width		5200# axle Spring (in lieu of 3500# axles) tandem	
8' Width		Woodlined (5/8" plywood) per trailer foot	
6" Additional Height (per 6")		E-Track (per 8 ft. track)	
RV-Style Camper Vent		E-Track Clips (ea)	
Ladder Rack (on top)		15" Full Spare (Tire & Wheel)	
Full Rear Drop Ramp		16" Full Spare (Tire & Wheel)	
V-Nose		Upgrade to 14-ply radial tires (each)	