CARGO 300TB — Tandem Axle Enclosed Trailer (Bumper Pull)

G.V.W.R	7,000 # to 10,400 #		Side Door	Full Size
Coupler	2" Coupler, 2 5/16" on 18' & 20'		Exterior Lights	D.O.T. Stop, Tail, Turn and Clearance
Axles	Tandem 3,500#, Tandem 5,200# Dexter		Interior Lights	2 Dome Lights (1 near each door)
Suspension	Eye-to-Eye Springs with Equalizer		Electric Plug	7-Way RV Style
Brakes	Electric brakes on all axles		Wiring	14 gauge in Conduit with Junction Box
Tire	16" Radials (15" radials on 14' and under)		Pre-Prep	3-Step Acid Washed with Phosphorus Solution
Wheel	16", 6-bolt (15" wheels on 14' and under)		Prep	Joints sealed with Polyurethane sealant
Frame	2 x 3 Angle		Primer	Rust Resistant Epoxy Primer
Tongue	3" Channel		Paint	Baked-on High Solid Urethane
Crossmembers	2 x 2 Angle on 16" centers		Pinstripes	Painted Pinstripes
Safety Chains	3/8' Heavy Duty with Safety Latch Hooks		Box Width	72" approx. standard
Jack	Top Wind with wheel		Deck Height	Approx. 14"
Sides	14 gauge smooth skin		Gravel Guard	Aluminum Diamondplate
Side Uprights	1 x 2 Tubing on 20" centers		Graphics	Optional
Floor	3/4" Treated Pine		Wiring	Front Mount in conduit
Roof	18 gauge Metal with Bows on 24" centers		Reflective Tape	Required D.O.T. Reflective Taping
Rear Door	Double Rear Van Doors		Safety	Emergency Breakaway switch & battery backup

Suggested Retail Price

Length	Width	Height	Axle	Tires	
12'	6'	6'	Tandem 3500 # Spring	15" Radial	
14'	6'	6'	Tandem 3500 # Spring	15" Radial	
16'	6'	6'	Tandem 3500 # Spring	16" Radial	
18'	6'	6'	Tandem 5200 # Spring	16" Radial	
20'	6'	6'	Tandem 5200 # Spring	16" Radial	

Options Pricing

6'8" Width		5200# axle Torsion (in lieu of 3500# axles) tandem	
7' OR 7'6" Width		5200# axle Spring (in lieu of 3500# axles) tandem	
8' Width		Full Rear Drop Ramp	
6" Additional Height (per 6")		Woodlined (5/8" plywood) per trailer foot	
RV-Style Camper Vent		E-Track (per 8 ft. track)	
Ladder Rack (on top)		E-Track Clips (ea)	
V-Nose		15" Full Spare (Tire & Wheel)	
Flip-up Side Mount Jack (in lieu of standard jack)		16" Full Spare (Tire & Wheel)	
		Upgrade to 14-ply radial tires (each)	