500 SERIES — Standard Livestock (Bumper Pull)

G.V.W.R	7,000 # & 10,400#		**Center Gate**	Standard Gate with spring-loaded slam latch
Coupler	2" Coupler (2 5/16" coupler on 18' & up)		**Rear Door**	Standard Full Swing with 1/2 Slider
Axles	Tandem 3,500#, Tandem 5,200# on 18' and up		**Rear Opening**	Tail Light Gussets, Pin/Spool Latch for Gate
Suspension	Dexter Eye-to-Eye Springs		**Fenders**	Steel Teardrop
Brakes	Electric brakes on all axles		**Window**	Large Oval in Front
Tire	Radial		**Wiring**	14 gauge in Conduit with Junction Box
Wheel	15" or 16" depending on length, 6-bolt		**Electric Plug**	7-Way RV Style
Spare	Spare Carrier Included		**Interior Lights**	None
Frame	2 x 3 Angle		**Exterior Lights**	D.O.T. Stop, Tail, Turn and Clearance
Tongue	3" Channel		**Pre-Prep**	3-Step Acid Washed with Phosphorus Solution
Crossmembers	2 x 2 Angle on 16" centers		**Prep**	Fenders & Roof Joints Sealed
Jack	Top Wind with wheel		**Primer**	Rust Resistant Epoxy Primer
Floor	2" Pressure Treated Pine		**Paint**	Baked-on High Solid Urethane
Sides	48" high embossed, 16 gauge		**Pinstripes**	Painted Pinstripes
Side Uprights	1 x 2 Tubing on 24" centers		**Deck Height**	Approx. 14"
Side Door	Standard Escape Door		**Gravel Guard**	Deluxe Aluminum Diamondplate
Roof	18 gauge Metal with Bows on 24" centers		**Reflective Tape**	Required D.O.T. Reflective Taping
Roof Radius	6" Roof Radius		**Safety**	Emergency Breakaway switch & battery backup
Nose Cap	Round, Square or V-Nose		**Safety Chains**	3/8' Heavy Duty with Safety Latch Hooks

Trailer shown with optional Full Spare Tire

Suggested Retail Price

Length	Width	Height	Center Gate	Axle	Tires	
10'	6'	6'6"	None	Tandem 3500 # Spring	15" Radial	
12'	6'	6'6"	Located Just behind Escape Door	Tandem 3500 # Spring	15" Radial	
14'	6'	6'6"	Set in Center	Tandem 3500 # Spring	15" Radial	
16'	6'	6'6"	Set in Center	Tandem 3500 # Spring	16" Radial	
18'	6'	6'6"	Set at 10' from Rear	Tandem 5200 # Spring	16" Radial	
20'	6'	6'6"	Set in Center	Tandem 5200 # Spring	16" Radial	

Options Pricing

6'8" Width		15" Full Spare (Tire & Wheel)	
7' OR 7'6" Width (axle upgrade may be required)		16" Full Spare (Tire & Wheel)	
8' Width (axle upgrade may be required)		Upgrade to 14-ply radial tires (each)	
6" Additional Height (per 6")		Interior Light	
Smooth Sides (14 gauge)		Woodlined (5/8") per ft.	
V-Nose		Solid Rear Gate (no slider)	
		Full Rear Drop Ramp (with mat)	