500 SERIES — Standard Livestock (Gooseneck)

G.V.W.R	7,000 # & 10,400#		Center Gate	Standard Gate with spring-loaded slam latch
Coupler	2 5/16" Gooseneck Coupler		Rear Door	Standard Full Swing with 1/2 Slider
Axles	Tandem 3,500#, Tandem 5,200# on 18' and up		Rear Opening	Tail Light Gussets, Pin/Spool Latch for Gate
Suspension	Dexter Eye-to-Eye Springs		Gooseneck Gate	Standard Gooseneck Gate
Brakes	Electric brakes on all axles		Fenders	Steel Teardrop
Tire	Radial		Window	None
Wheel	15" or 16" depending on length, 6-bolt		Wiring	14 gauge in Conduit with Junction Box
Spare	Spare Carrier Included		Electric Plug	7-Way RV Style
Frame	3 x 3 Angle		Interior Lights	None
Gooseneck	6" Channel		Exterior Lights	D.O.T. Stop, Tail, Turn and Clearance
Crossmembers	2 x 2 Angle on 16" centers		Pre-Prep	3-Step Acid Washed with Phosphorus Solution
Jack	12,00# Drop Leg Jack (Spring -Loaded)		Prep	Fenders & Roof Joints Sealed
Floor	2" Pressure Treated Pine		Primer	Rust Resistant Epoxy Primer
Sides	48" high embossed, 16 gauge		Paint	Baked-on High Solid Urethane
Side Uprights	1 x 2 Tubing on 24" centers		Pinstripes	Painted Pinstripes
Side Door	Full Escape Door		Deck Height	Approx. 14"
Roof	18 gauge Metal with Bows on 24" centers		Gravel Guard	Deluxe Aluminum Diamondplate
Roof Radius	6" Roof Radius		Reflective Tape	Required D.O.T. Reflective Taping
Nose Cap	Round, Square or V-Nose		Safety	Emergency Breakaway switch & battery backup
			Safety Chains	3/8' Heavy Duty with Safety Latch Hooks

Trailer shown with optional V-Nose.

Round or Square is standard.

Suggested Retail Price

Length	Width	Height	Center Gate	Axle	Tires	
10'	6'	6'6"	None	Tandem 3500 # Spring	15" Radial	
12'	6'	6'6"	Located Just behind Escape Door	Tandem 3500 # Spring	15" Radial	
14'	6'	6'6"	Set in Center	Tandem 3500 # Spring	15" Radial	
16'	6'	6'6"	Set in Center	Tandem 3500 # Spring	16" Radial	
18'	6'	6'6"	Set at 10' from Rear	Tandem 5200 # Spring	16" Radial	
20'	6'	6'6"	Set in Center	Tandem 5200 # Spring	16" Radial	

Options Pricing

6'8" Width		15" Full Spare (Tire & Wheel)	
7' OR 7'6" Width (axle upgrade may be required)		16" Full Spare (Tire & Wheel)	
8' Width (axle upgrade may be required)		Upgrade to 14-ply radial tires (each)	
6" Additional Height (per 6")		Interior Light	
Smooth Sides (14 gauge)		Woodlined (5/8") per ft.	
V-Nose		Solid Rear Gate (no slider)	
		Full Rear Drop Ramp (with mat)	