

500 ES

Economy Livestock (Bumper Pull)

G.V.W.R	7,000 #	CENTER GATE	Standard Gate with spring-loaded slam latch
COUPLER	2" Coupler (2 5/16" coupler on 18' & up)	REAR DOOR	Standard Full Swing with 1/2 Slider
AXLES	Tandem 3,500#	REAR OPENING	Tail Light Gussets, Pin/Spool Latch for Gate
SUSPENSION	Dexter Eye-to-Eye Springs	FENDERS	Steel Teardrop
BRAKES	Electric brakes on one axle (check local law for compliance)	WINDOW	None
TIRE	15" Radial	WIRING	14 gauge in Conduit with Junction Box
WHEEL	15", 6-bolt	ELECTRIC PLUG	7-Way RV Style
SPARE	Spare Carrier Included	INTERIOR LIGHTS	None
FRAME	2 x 3 Angle	EXTERIOR LIGHTS	D.O.T. Stop, Tail, Turn and Clearance
TONGUE	3" Channel	PRE-PREP	3-Step Acid Washed with Phosphorus Solution
CROSSMEMBERS	2 x 2 Angle on 16" centers	PREP	Fenders & Roof Joints Sealed
JACK	Top Wind with wheel	PRIMER	Rust Resistant Epoxy Primer
FLOOR	2" Pressure Treated Pine	PAINT	Baked-on High Solid Urethane
SIDES	48" high embossed, 16 gauge	PINSTRIPES	Painted Pinstripes
SIDE UPRIGHTS	1 x 2 Tubing on 38" centers (approx.)	DECK HEIGHT	Approx. 14"
SIDE DOOR	Standard Escape Door	GRAVEL GUARD	Deluxe Aluminum Diamondplate
ROOF	18 gauge Metal with Bows on 24" centers	REFLECTIVE TAPE	Required D.O.T. Reflective Taping
ROOF RADIUS	6" Roof Radius	SAFETY	Emergency Breakaway switch & battery backup
NOSE CAP	Standard Aerodynamic Front	SAFETY CHAINS	3/8" Heavy Duty with Safety Latch Hooks



SUGGESTED RETAIL PRICE

Length	Width	Height	Center Gate	Axle	Tires
12'	6'	6'6"	Located Just behind Escape Door	Tandem 3500 # Spring, Brakes on one axle	15" Radial
14'	6'	6'6"	Set in Center	Tandem 3500 # Spring, Brakes on one axle	15" Radial
16'	6'	6'6"	Set in Center	Tandem 3500 # Spring, Brakes on one axle	15" Radial

OPTIONS PRICING

6" Additional Height (per 6")		Interior Light	
Upgrade to 16", 10-ply radial tires (per trailer)		Full Rear Drop Ramp (with mat)	
4-Wheel Electric Brakes		Add for full Metal Nose Cap (in lieu of tapered metal front)	
5' wide		V-Nose	
15" Full Spare (Tire & Wheel)		add Oval Window in front (per window)	