

# 600 DELUXE

# Deluxe Livestock (Bumper Pull)

<b>G.V.W.R</b>	7,000 # & 10,400#	<b>CENTER GATE</b>	Standard Gate with spring-loaded slam latch
<b>COUPLER</b>	2" Coupler (2 5/16" coupler on 18' & up)	<b>REAR DOOR</b>	Full Swing with 1/2 Slider on Rollers
<b>AXLES</b>	Tandem 3,500#, Tandem 5,200# on 18' and 20'	<b>REAR OPENING</b>	3x5 Tubing Uprights with Slam Latch for Gate
<b>SUSPENSION</b>	Dexter Torflex	<b>FENDERS</b>	Steel Teardrop
<b>BRAKES</b>	Electric brakes on all axles	<b>WINDOW</b>	Large Oval in Front
<b>TIRE</b>	Radial	<b>WIRING</b>	14 gauge in Conduit with Junction Box
<b>WHEEL</b>	15" or 16" depending on length, 6-bolt	<b>ELECTRIC PLUG</b>	7-Way RV Style
<b>SPARE</b>	Spare Carrier Included	<b>INTERIOR LIGHTS</b>	Standard Dome Lights
<b>FRAME</b>	2 x 3 Angle	<b>EXTERIOR LIGHTS</b>	All DOT Required Lighting plus Quad Tail Lights
<b>TONGUE</b>	3" Channel	<b>PRE-PREP</b>	3-Step Acid Washed with Phosphorus Solution
<b>CROSSMEMBERS</b>	2 x 2 Angle on 16" centers	<b>PREP</b>	All Joints Sealed with Polyurethane
<b>JACK</b>	Top Wind with wheel	<b>PRIMER</b>	Rust Resistant Epoxy Primer
<b>FLOOR</b>	2" Pressure Treated Pine	<b>PAINT</b>	Baked-on High Solid Urethane
<b>SIDES</b>	48" high embossed, 16 gauge	<b>PINSTRIPES</b>	Painted Pinstripes
<b>SIDE UPRIGHTS</b>	1 x 2 Tubing on 24" centers	<b>DECK HEIGHT</b>	Approx. 14"
<b>SIDE DOOR</b>	Standard Escape Door	<b>GRAVEL GUARD</b>	Aluminum Diamondplate
<b>ROOF</b>	18 gauge Metal with Bows on 24" centers	<b>REFLECTIVE TAPE</b>	Required D.O.T. Reflective Taping
<b>ROOF RADIUS</b>	6" Roof Radius	<b>SAFETY</b>	Emergency Breakaway switch & battery backup
<b>NOSE CAP</b>	Round, Square or V-Nose (optional)	<b>SAFETY CHAINS</b>	3/8" Heavy Duty with Safety Latch Hooks



### SUGGESTED RETAIL PRICE

Length	Width	Height	Center Gate	Axle	Tires
10'	6'	6'6"	None	Tandem 3500 # Torsion	15" Radial
12'	6'	6'6"	Located Just behind Escape Door	Tandem 3500 # Torsion	15" Radial
14'	6'	6'6"	Set in Center	Tandem 3500 # Torsion	15" Radial
16'	6'	6'6"	Set in Center	Tandem 3500 # Torsion	16" Radial
18'	6'	6'6"	Set at 10' from Rear	Tandem 5200 # Torsion	16" Radial
20'	6'	6'6"	Set in Center	Tandem 5200 # Torsion	16" Radial

### OPTIONS PRICING

6'8" Width		15" Full Spare (Tire & Wheel)	
7' OR 7'6" Width (axle upgrade may be required)		16" Full Spare (Tire & Wheel)	
8' Width (axle upgrade may be required)		Upgrade to 14-ply radial tires (each)	
6" Additional Height (per 6")		Extra Interior Light	
Smooth Sides (14 gauge)		Woodlined (5/8") per ft.	
V-Nose Front		Solid Rear Gate (no slider)	
		Full Rear Drop Ramp (with mat)	